



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

* 1 Identification

- **Product Identifier**
- **Trade Name:** Quick
- **Product Number:** SM-14
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:** Mild Alkaline Cleaner
- **Application of the substance / the mixture:** Industry Specific Application
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Nor Cal Pressure Washer Equipment
250 South Maple
G
South San Francisco, CA 94080
+1-650-952-9997
g9786@aol.com
www.norcalpressurewash.com
- **Emergency telephone number:** 1-800-424-9300 (CHEMTREC)



2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Acute Tox. 4 H302 Harmful if swallowed.
 Acute Tox. 4 H312 Harmful in contact with skin.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 STOT SE 3 H335 May cause respiratory irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Warning
- **Hazard-determining components of labeling:**
Disodium Metasilicate
2-butoxyethanol
COMPLEX ALKYL PHOSPHATE ESTER
Pentasodium triphosphate
- **Hazard statements:**
H302+H312 Harmful if swallowed or in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
- **Precautionary statements:**
P260 Do not breathe fume.



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

- P262 Do not get in eyes, on skin, or on clothing.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P301+P312 If swallowed: Call a doctor if you feel unwell.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332+P313 If skin irritation occurs: Get medical advice.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:


This value refers to knowledge of known, established toxicological or ecotoxicological values. 10 % of the mixture consists of component(s) of unknown toxicity.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Hazard(s) not otherwise classified (HNOC): None known

*** 3 Composition/Information on Ingredients**

Chemical characterization: Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous Components:

CAS: 10101-89-0	Trisodium Phosphate Dodecahydrate ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318	0-10%
CAS: 7758-29-4	Pentasodium triphosphate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0-10%
CAS: 6834-92-0	Disodium Metasilicate ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; STOT SE 3, H335	0-10%
CAS: 111-76-2 RTECS: KJ 8575000	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	0-10%

(Contd. on page 3)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

CAS: 9016-45-9	Nonylphenoxy poly(ethyleneoxy)ethanol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	0-10%
CAS: 68130-47-2	COMPLEX ALKYL PHOSPHATE ESTER ⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 2, H401	0-10%

• **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

* 4 First-Aid Measures

• **Description of first aid measures**

• **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• **After inhalation:**

Give oxygen or artificial respiration if needed. If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

• **After skin contact:**

Take off contaminated clothing and shoes immediately. Promptly flush skin with water for at least 15 minutes to ensure all chemical is removed. If reddening develops and/or persists, obtain medical attention.

• **After eye contact:**

Flush with large amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. If eye irritation persists, obtain medical attention.

• **After swallowing:**

Rinse mouth with water. Give 3-4 glasses of water or milk to dilute stomach contents. Do NOT induce vomiting. If vomiting occurs, give more water or milk. Never give anything by mouth to an unconscious person. Get immediate medical attention.

• **Information for doctor**

• **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

• **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

* 5 Fire-Fighting Measures

• **Extinguishing media**

• **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

• **For safety reasons unsuitable extinguishing agents:** No further relevant information.

• **Special hazards arising from the substance or mixture:**

- Carbon Oxides
- Nitrogen Oxides (NOx)
- Phosphorous Oxides
- Silicon Oxides
- Sodium Oxides
- Sulfur Oxides

• **Advice for firefighters**

• **Special protective equipment for firefighters:**

Mouth respiratory protective device.



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

* 6 Accidental Release Measures

• **Personal precautions, protective equipment and emergency procedures:**

- Use personal protective equipment.
- Keep from contacting skin or eyes.
- Avoid breathing vapors, mist or gas.
- Ensure adequate ventilation.
- Evacuate personnel to safe areas.

• **Environmental precautions:** Do not allow to enter sewers/surface or ground water.

• **Methods and material for containment and cleaning up:**

- Use neutralizing agent.
- Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.
- Dispose of the collected material according to regulations.

• **Reference to other sections:**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

• **Protective Action Criteria for Chemicals**

• **PAC-1:**

7758-29-4	Pentasodium triphosphate	0.61 mg/m ³
6834-92-0	Disodium Metasilicate	3.8 mg/m ³
111-76-2	2-butoxyethanol	60 ppm
9016-45-9	Nonylphenoxy poly(ethyleneoxy)ethanol	43 mg/m ³

• **PAC-2:**

7758-29-4	Pentasodium triphosphate	6.8 mg/m ³
6834-92-0	Disodium Metasilicate	42 mg/m ³
111-76-2	2-butoxyethanol	120 ppm
9016-45-9	Nonylphenoxy poly(ethyleneoxy)ethanol	470 mg/m ³

• **PAC-3:**

7758-29-4	Pentasodium triphosphate	620 mg/m ³
6834-92-0	Disodium Metasilicate	250 mg/m ³
111-76-2	2-butoxyethanol	700 ppm
9016-45-9	Nonylphenoxy poly(ethyleneoxy)ethanol	5,400 mg/m ³

* 7 Handling and Storage

• **Handling**

• **Precautions for safe handling:**

- Avoid breathing vapors or mist.
- Avoid contact with eyes, skin, or clothing.
- Use approved, original containers only.
- Keep containers closed when not in use.
- Do not expose containers to open flame, excessive heat, or direct sunlight.
- Do not puncture or drop containers.



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

- Handle with care and avoid spillage on the floor.
- Keep material out of reach of children.
- Keep material away from incompatible materials.
- Wash thoroughly after handling.
- Ensure adequate ventilation.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Keep away from heat, sparks and flames.

Do not store in direct sunlight.

Store away from strong acids, strong bases, strong oxidizing agents, strong reducing agents, Lead, Tin & Tin Oxides, reactive metals (Zinc & Aluminum) and their alloys (Brass), Alkali metals (Lithium, Sodium, Potassium, etc.), Copper and its alloys, Nickel and galvanized surfaces.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s):** No further relevant information available.

*** 8 Exposure Controls/Personal Protection**

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

- **Components with occupational exposure limits:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

10101-89-0 Trisodium Phosphate Dodecahydrate	
STEL/WEEL	Short-term value: 5 mg/m ³
111-76-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

- **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol	
BEI	200 mg/g creatinine urine end of shift Butoxyacetic acid with hydrolysis

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

• **Breathing equipment:**

Have self-contained breathing apparatus, positive pressure, MSHA/NIOSH (approved or equivalent) available in case of spillage or equipment failure.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Select glove material based on penetration times, rates of diffusion and degradation.

• **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Viton, Nitrile or Buna rubber.

• **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• **Eye protection:**



Safety glasses

• **Limitation and supervision of exposure into the environment:** None

* 9 Physical and Chemical Properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Liquid
Color: Clear, light brown
Odor: Faint, sweet
Odor threshold: Not determined.

• **pH-value @ 20 °C (68 °F):** 11.3-12.0

• **Change in condition**

Melting point/Melting range: Not determined.
Boiling point/Boiling range: Not determined.

• **Flash point:** None

• **Flammability (solid, gaseous):** Not determined.

• **Ignition temperature:** Not applicable

(Contd. on page 7)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapor pressure:** Not applicable.
- **Density @ 20 °C (68 °F):** 1.087 g/cm³ (9.071 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** Not applicable.
- **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - Water:** Fully Soluble
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not applicable.
 - Kinematic:** Not applicable.
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Incompatibilities, flames, ignition sources.
- **Incompatible materials:** Strong acids, strong bases, strong oxidizing agents, strong reducing agents, Lead, Tin & Tin Oxides, reactive metals (Zinc & Aluminum) and their alloys (Brass), Alkali metals (Lithium, Sodium, Potassium, etc.), Copper and its alloys, Nickel and galvanized surfaces.
- **Hazardous decomposition products:** Carbon Oxides, Nitrogen Oxides (NOx), Phosphorous Oxides, Silicon Oxides, Sodium Oxides and Sulfur Oxides.

* 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

LD/LC50 values that are relevant for classification:		
10101-89-0 Trisodium Phosphate Dodecahydrate		
Oral	LD50	7,400 mg/kg (Rat)
7758-29-4 Pentasodium triphosphate		
Oral	LD50	3,900 mg/kg (Rat)

(Contd. on page 8)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

6834-92-0 Disodium Metasilicate		
Oral	LD50	1,280 mg/kg (Rat)
111-76-2 2-butoxyethanol		
Oral	LD50	470 mg/kg (Rat)
Dermal	LD50	220 mg/kg (rab)
Inhalative	LC50/4 h	2,174.91 mg/l (Rat)
9016-45-9 Nonylphenoxy poly(ethyleneoxy)ethanol		
Oral	LD50	3,310 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
68130-47-2 COMPLEX ALKYL PHOSPHATE ESTER		
Inhalative	LC50/96 hours	5.5 mg/l (Trout)
		3,950 mg/l (Rat)

- **Primary irritant effect:**
- **On the skin:** Strong caustic effect on skin and mucous membranes.
- **On the eye:**
Irritating effect.
Corrosive effect.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

111-76-2	2-butoxyethanol	3
----------	-----------------	---

- **NTP (National Toxicology Program):**
None of the ingredients are listed.
- **OSHA-Ca (Occupational Safety & Health Administration):**
None of the ingredients are listed.

12 Ecological Information

- **Toxicity:**
 - **Aquatic toxicity:**
- | | | |
|--|----------|--------------|
| 6834-92-0 Disodium Metasilicate | | |
| EC50 | 247 mg/l | (Water flea) |



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

111-76-2 2-butoxyethanol	
EC50	1,815 mg/l (Water flea)
9016-45-9 Nonylphenoxy poly(ethyleneoxy)ethanol	
EC50	12 mg/l (Algae - Selenastrum capricornutum) (96 HOURS)
	0.148 mg/l (Daphnia) (48 hours)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**
Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADN, IMDG, IATA** Non-Regulated Material
- **ADR/ADN** UN-
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

(Contd. on page 10)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

* 15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

• **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

• **Section 313 (Specific toxic chemical listings):**

7758-29-4	Pentasodium triphosphate
111-76-2	2-butoxyethanol
9016-45-9	Nonylphenoxy poly(ethyleneoxy)ethanol

• **TSCA (Toxic Substances Control Act):**

7758-29-4	Pentasodium triphosphate	ACTIVE
6834-92-0	Disodium Metasilicate	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
9016-45-9	Nonylphenoxy poly(ethyleneoxy)ethanol	ACTIVE
68130-47-2	COMPLEX ALKYL PHOSPHATE ESTER	ACTIVE

• **Hazardous Air Pollutants**

None of the ingredients are listed.

• **California Proposition 65:**

• **Chemicals known to cause cancer:**

None of the ingredients are listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

• **New Jersey Right-to-Know List:**

111-76-2	2-butoxyethanol
----------	-----------------

• **New Jersey Special Hazardous Substance List:**

111-76-2	2-butoxyethanol	CA, F2
----------	-----------------	--------

• **Pennsylvania Right-to-Know List:**

10101-89-0	Trisodium Phosphate Dodecahydrate
7758-29-4	Pentasodium triphosphate
111-76-2	2-butoxyethanol

• **Pennsylvania Special Hazardous Substance List:**

10101-89-0	Trisodium Phosphate Dodecahydrate	E
7758-29-4	Pentasodium triphosphate	E

(Contd. on page 11)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

• **Carcinogenic categories:**

• **EPA (Environmental Protection Agency):**

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

• **TLV (Threshold Limit Value established by ACGIH):**

111-76-2	2-butoxyethanol	A3
----------	-----------------	----

• **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

• **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms:**



• **Signal word:** Warning

• **Hazard-determining components of labeling:**

Disodium Metasilicate
 2-butoxyethanol
 COMPLEX ALKYL PHOSPHATE ESTER
 Pentasodium triphosphate

• **Hazard statements:**

H302+H312 Harmful if swallowed or in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

• **Precautionary statements:**

P260 Do not breathe fume.
 P262 Do not get in eyes, on skin, or on clothing.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
 P301+P312 If swallowed: Call a doctor if you feel unwell.
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 If skin irritation occurs: Get medical advice.
 P363 Wash contaminated clothing before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/17/2019

Reviewed on 04/17/2019

Trade Name: Quick

· **National regulations:**

None of the ingredients are listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of last revision/ revision number:** 04/17/2019 / 16

· **Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMSIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety and Health
- OSHA: Occupational Safety & Health Administration
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit
- Flam. Liq. 4: Flammable liquids – Category 4
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Corr. 1A: Skin corrosion/irritation – Category 1A
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106